



146 Duchaine Blvd.  
 New Bedford, MA 02745  
 Tel. 508/995-9711, Fax # 508/995-5021  
 e-Mail: pumps@edsonint.com

## 161-A-2153 Explosion Proof Momentary Start/Stop Switch



### General:

The Edson 161-A-2153 explosion proof start/stop is designed for hazardous locations. Fuel docks, industrial processes or any situation where volatile fuels and vapors could be present. The momentary contacts connect in the same way as our hose stands (260-284) and remote remote switches (161-A-1613)

### Technical Specs

• Item:	<b>Control Station</b>
• Number of Gangs:	<b>1</b>
• Number of Operators:	<b>2</b>
• Contact Rating:	<b>10A @ 600VAC, 2.5A @ 250VDC</b>
• Hub Style:	<b>Feed-Thru</b>
• Hub Size:	<b>1/2"</b>
• Type of Operator:	<b>Push Button</b>
• Action:	<b>Momentary</b>
• Contact Form:	<b>1NO/1NC</b>
• Series:	<b>FXCS</b>
• Operator Color:	<b>Green/Red</b>
• NEMA Contact Rating Designation:	<b>A600/Q300</b>
• NEMA Rating:	<b>7, 9</b>
• Legend:	<b>Start/Stop</b>
• Mounting:	<b>Surface</b>
• Height:	<b>6.81"</b>
• Width:	<b>3.6875"</b>
• Depth:	<b>5.344"</b>
• Enclosure Material:	<b>Cast Aluminum</b>
• Standards:	<b>UL, CSA</b>
• Safety Rating:	<b>Class 1, Division 1, Groups C, D</b>