



146 Duchaine Blvd.  
 New Bedford, MA 02745  
 Tel. 508/995-9711, Fax # 508/995-5021  
 e-Mail: pumps@edsonint.com

## Explosion Proof Upgrade 28624/28623/28621 Part # 161-A-3275

- HP: 3
- Voltage: 230/460
- kW: 2.24
- FL Amps: 8/4
- RPM: 1800
- FL Eff: 90.2 %
- SF: 1.0
- HP: 2
- Voltage: 190/380
- kW: 1.49
- FL Amps: 6.8/3.4
- RPM: 1500
- FL Eff: 88.5 %
- SF: 1.0
- Phase: 3
- Insulation Class: F
- Frame: 182TC
- Duty: CONTINUOUS
- Enclosure: EPFC
- Ambient: 40
- Mounting: C-Face Footless
- NEMA Design: B
- Orientation: HORIZONTAL
- Starting Type: ACROSS THE LINE
- Assembly: F1 ONLY
- KVA Code: K
- Drive End Bearing: BALL
- IP Code: 54
- Opposite End Bearing: BALL
- Drive End Bearing Size: 6207
- Opposite End Bearing Size: 6206
- Hazardous Location: EXP PROOF CL I GR D CL II GR F&G T3B
- Weight: 164 lbs.
- CE: N
- CSA: N
- UL: UL Listed
- Thermal Protection: Thermostats (Normally Closed)
  - Ship Weight (lbs): 164

