

The 2500 Double Diaphragm Pump **Pump Out Station Application**

PERFORMANCE FEATURES

- Pump Rated to 25 gpm (94.6 lpm)
- Discharge Head Up to 25 ft / 7.62 m (10.8 psi)
- Suction Head Up to 25 ft / 7.62 m (23" Hg)
- Dependable Performance

DESIGN FEATURES

- Double Diaphragm Pump with Common Inlet & Discharge
- 3/4 HP(.55kw) / 110V Motor Drive
- Stop/Start With Intergral Run Timer
- So Easy To Install and Maintain.



Edson's New 2500 Pump is an outstanding•multi-functional•electric powered double diaphragm
plastic
transfer pump.

- •Because the Model 2500 has the ability to suck sewage from a boat with a powerful vacuum
- Because the Model 2500 has the flexibility to meet most installation conditions
- •Because the Model 2500 is designed and built in a simple to understand and easy to maintain package
- •Because the Model 2500 is made of a corrosion proof, glass reinforced, polypropylene
- •Because the Model 2500 can be combined with a variety of optional Edson pump out accessories

Designing a pump out system for your marina with the Model 2500 will be one of the best decisions you will make this year.

THE 2500 WITH POPULAR PUMP OUT STATION OPTIONS

2500 PUMP PERFORMANCE :

- •Max Volume 25 gpm / 94.6 lpm / 5.68 m³hr.
- Primed Suction Lift to 25 ft /7.62 meters
- •Discharge Head to 25 ft / 7.62 meters

2500 PUMP CONSTRUCTION :

- Polypropylene Pump Body
- •Inlet & Discharge Ports 1.5" MNPT Polypropylene
- •3/4hp(.55kw); 60/50hz; tefc Intergral Gearmotor
- Check Valves Viton Enclosed In Clear PVC

161-B-1366-304 ENCLOSURE :

- •304 Stainless (316 available)
- Modular 4 Part Assembly For Added Strength, Easy Assembly and Access
- •On/Off Switches and Hour Meter Installed In Front Panel

160-A-2876 HOSE RACK :

•Hose Rack Holds Up To 75 ft of Pump Out Hose

●304 Stainless 261-25-150 PUMP OUT HOSE ASSEMBLY :

- •Flexible Smooth Bore 1 1/2" Hose
- •90⁰ Ball Valve, Clear Sight Glass, Female Quick Clamp Adapter
- Complete Set Of Clamp In Deck Adapters

160-B-1363 DECK FITTING RACK :

•Holds All Deck Fittings That Come With An Edson Pump Out Hose Assembly 304 Stainless



Holding Tank

Pumpout

Station

EDSØN

w Bedford, MA, USA

OPTIONS & ACCESSORIES

iding Ta

Enclosures

Stainless Steel With Hour Meter and Stop/Start 304SS Order No. 161-B-1366-304 316SS Order No. 161-B-1366-316

Dim. 26"(66cm) X 26"(66cm) X 32"(96.5cm)

Heavy Duty Fiberglass White Gelcoat Finish Order No. 161-B-808 Dim. 28"(71.1cm) X 26"(66cm) X 38"(96.5cm)

Hose Stands & Hose Rack

White Powder Coated Aluminum Hose Stands Hold Up to 100 ft of 1 1/2" Pump Out Hose Basic Stand Order No. 260-HS Stand With Start/ Stop Switches Order No. 260-284 Stand With Token Operated Switch Order No. 260-Token

Stainless Steel Hose Stand Hold Up to 100 ft of 1 1/2" Pump Out Hose Electropolished 304SS Order No. 260-SS

Stainless Steel Hose Rack Hold Up to 75ft of 1 1/2" Pump Out Hose 304SS Order No. 160-A-2876 Mounts to any vertcal surface including enclosures.

Pump Out Hose Assemblies

Light Weight Flexable Abashion Resistant 1 1/2" Suction Hose Standard Length Assemblies Come Complete With Ball Valve Sight Glass and All Quick Clamp Deck Adapters. 25 ft Assembly Order No. 261-25-150 50 ft Assembly Order No. 261-50-150

Optional Length Hose Assemblies Up To 100 ft In Length Edson can provide any continuous length pump out hose from 5 ft to 100ft. Whatever is required for the installation

Deck Fitting Rack Holds All The Standard Deck Fitting Adapters Electropolished 304SS Order No. 160-B-1363



Edsen

Holding Tank Pumpout

Station

Accessories For Inslip Pump Outs Hydrantse Recessed Hydrant Containere Hose Handlere Radio Remote Start/Stop System



146 Duchaine Blvd., New Bedford, MA 02745-1292 Tel. 508-995-9711 Fax 508-995-5021 E-Mail pumps@edsonintl.com